



GLOCK 19 Gen6



FRONT SIGHT
polymer



SLIDE STOP LEVER
ambidextrous

TRIGGER CONFIGURATION
triggerspring01 / connector 5 /
firing pin spring 24N (silver)



REAR SIGHT
polymer



MAGAZINE
15 rds



MAGAZINE CATCH
reversible



PERFECTION

Technical data are rounded and do not reflect any tolerances – they may be altered without notice.

www.glock.com



DIMENSIONS

	mm	in.
1. LENGTH (OVERALL)	185	7,28
2. SLIDE LENGTH (cpl.)	174	6,85
3. WIDTH (OVERALL)	34,4	1,35
4. SLIDE WIDTH	25,5	1,00
5. HEIGHT INCL. MAGAZINE	128	5,04
6. SIGHT RADIUS (POLYMER)	157	6,18
SIGHT RADIUS (STEEL)	156	6,14
SIGHT RADIUS (GNS)	155	6,10
7. TRIGGER DISTANCE	70	2,76
8. BARREL DISTANCE	20	0,79

VARIABLE DIMENSIONS

		mm	in.
MEDIUM BACKSTRAP w/o beaver tail (+ 2 mm 0.08 in.)	1. LENGTH (OVERALL)	187	7,36
	7. TRIGGER DISTANCE	72	2,83
LARGE BACKSTRAP w/o beaver tail (+ 4 mm 0.16 in.)	1. LENGTH (OVERALL)	189	7,44
	7. TRIGGER DISTANCE	74	2,91

TECHNICAL DATA



CALIBER

9x19



MAG. CAPACITY

15 rds



BARREL PROFILE

hexagonal (GMB)



BARREL LENGTH

mm	in.
102	4,02



LENGTH OF TWIST

mm	in.
250	9,84



WEIGHT

without magazine	
g	oz
570	20,11



WEIGHT

with empty magazine	
g	oz
640	22,58



WEIGHT*

with loaded magazine	
g	oz
825	29,10



TRIGGER TRAVEL

mm	in.
12,5	0,49

TRIGGER PULL

N	lbf
26	5,8

* depending on the ammunition used